

SelfLube Ski Lift Bushings

- **Made of C954** - one of the finest bearing materials available
- **150 times stronger than polymer bushings** - based upon modulus of elasticity
- **Thermal conductivity 200 times that of polymer bushings** - heat caused by normal friction is quickly dissipated away. This prevents heat buildup, which shortens bushing life.
- **The Gummy Factor** - the material we use has a natural tendency to pull and stretch rather than cleanly cut. This is great for durability because it reduces tearing and gouging caused by any shaft surface roughness.
- **Tight tolerances** - for interchangeability, improved longevity and a trouble free install

2 Versions Available



Standard



Grease Groove

Size Range				
	Inch		Metric	
	Min	Max	Min	Max
I.D.	0.750	6.000	19	152
O.D.	1.125	7.000	29	178
Length	0.500	8.000	13	203
Wall Thickness	0.120*	0.500	3*	12

Tolerances			
	ID	OD	L
Inch	+0.001/-0	+0.001/-0	+/- .004
Metric	+0.025/-0	+0.025/-0	+/-0.2

* May not apply to larger sizes

Placing an Order or Requesting a Quote

We make things simple. You don't need to look up a part number. Just order by bushing size. Designate Grease Groove with GG at the end.

Ordering Examples		
Version	Inch	Metric
Standard	SKI 1.750 ID x 2.000 OD x 2.500 L	SKM 40.0 ID x 47.0 OD x 50 L
Grease Groove	SKI 1.750 ID x 2.000 OD x 2.500 L GG	SKM 40.0 ID x 47.0 OD x 50 L GG

Call or Email us today 616-837-9721 info@selflube.com